

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
22 January 2004 (22.01.2004)


PCT

(10) International Publication Number  
WO 2004/007934 A1

- (51) International Patent Classification<sup>7</sup>: F02D 41/40, F02M 47/02
- (21) International Application Number: PCT/GB2003/003015
- (22) International Filing Date: 11 July 2003 (11.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0216347.5 13 July 2002 (13.07.2002) GB
- (71) Applicant (for all designated States except US): DELPHI TECHNOLOGIES, INC. [US/US]; P.O. Box 5052, Troy, MI 48007 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): HARCOMBE, Anthony, Thomas [GB/GB]; 1 Warren Avenue, Richmond, Surrey TW10 5DZ (GB). DODDS Andrew [GB/GB]; 21 Van Diemens Close, Chinnor, Oxfordshire OX39 4QE (GB).
- (74) Agents: KELTIE, David, Arthur et al.; David Keltie Associates, Fleet Place House, 2 Fleet Place, London EC4M 7ET (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent

[Continued on next page]

(54) Title: CONTROL METHOD



(57) Abstract: A control method for a fuel injection system having a spill valve (20), a nozzle control valve (22) and a valve needle (12) which is engageable with a seating to control fuel injection, wherein the method comprises applying a first drive current signal (30) to the spill valve (22) to move the spill valve (22) into a closed state and applying a second drive current signal (40) to the nozzle control valve (22) to move the nozzle control valve (22) to an open state, thereby to lift the valve needle (12) from the seating to initiate a main injection of fuel. The first drive current signal (30) is modified so as to move the spill valve (20) to an open state during "a spill valve opening period" during which the second drive current signal (40) is modified to move the nozzle control valve (22) from the open state to a closed state. As a result the valve needle (12) is seated to terminate the main injection of fuel.

BEST AVAILABLE COPY

WO 2004/007934 A1

WO 2004/007934 A1



(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

**BEST AVAILABLE COPY**